

REPORT DOCUMENTATION PAGE				<i>Form Approved OMB No. 0704-0188</i>	
<small>The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to the Department of Defense, Executive Services and Communications Directorate (0704-0188). Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.</small>					
PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ORGANIZATION.					
1. REPORT DATE (DD-MM-YYYY)		2. REPORT TYPE		3. DATES COVERED (From - To)	
4. TITLE AND SUBTITLE				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT	b. ABSTRACT	c. THIS PAGE			19b. TELEPHONE NUMBER (Include area code)

PUBLICATION OR PRESENTATION RELEASE REQUEST

Pubkey: 9620

NRLINST 0.40

15-1231-1322

1. REFERENCES AND ENCLOSURES	2. TYPE OF PUBLICATION OR PRESENTATION	3. ADMINISTRATIVE INFORMATION
Ref: (a) NRL Instruction 5600.2 (b) NRL Instruction 5510.40E Encl: (1) Two copies of subject publication/presentation	<input type="checkbox"/> Abstract only, published <input type="checkbox"/> Book author <input type="checkbox"/> Book editor <input checked="" type="checkbox"/> Conference Proceedings (refereed) <input type="checkbox"/> Journal article (refereed) <input type="checkbox"/> Oral Presentation, published <input type="checkbox"/> Video <input type="checkbox"/> Poster <input type="checkbox"/> Abstract only, not published <input type="checkbox"/> Book chapter <input type="checkbox"/> Multimedia report <input type="checkbox"/> Conference Proceedings (not refereed) <input type="checkbox"/> Journal article (not refereed) <input type="checkbox"/> Oral Presentation, not published <input type="checkbox"/> Other, explain	STRN NRL/PP/7330-15-2537 Route Sheet No. 7330/ Job Order No. 73-4951-05-5 Classification U S C FOUO Sponsor ONR BASE 6.1 Bay Sponsor's approval yes (attached) (*Required if research is other than 5.1/5.2 NRL or ONR unclassified research or if publication/presentation is classified)
ALL DOCUMENTS/PRESENTATIONS MUST BE ATTACHED		
4. AUTHOR		
Title of Paper or Presentation Optical Turbulence in the Ocean AUTHOR(s) LEGAL NAME(s) OF RECORD (First, MI, Last), CODE, (Affiliation if not NRL). Wellin Hou 7333. This paper will be presented at the OSA Imaging and Applied Optics Meeting (Name of Conference) 07-JUN - 11-JUN-15, Arlington, VA, Unclassified (Date, Place and Classification of Conference) and/or for published in OSA Imaging and Applied Optics Meeting, Unclassified (Name and Classification of Publication)		
5. CERTIFICATION OR CLASSIFICATION		
It is my opinion that the subject paper (is <input type="checkbox"/>) (is not <input checked="" type="checkbox"/>) classified, in accordance with reference (b) and this paper does not violate any disclosure of trade secrets or suggestions of outside individuals or concerns which have been communicated to the NRL in confidence. This subject paper (has <input type="checkbox"/>) (has never <input checked="" type="checkbox"/>) been incorporated in an official NRL Report. Wellin Hou, 7333 Name and Code (Principal Author) (Legal Name of Record and Signature Only) (Signature)		
6. ROUTING/APPROVAL (NOTE: If name other than your legal name of record is annotated on the publication or presentation itself, add an explanatory note in the "comments" section below next to your signed legal name of record)		
CODE	SIGNATURE	DATE
Co-Author(s) Wellin Hou, 7333	<i>Wellin Hou</i>	4/8/15
Section Head	<i>Wellin Hou</i>	
Branch Head Richard L. Crout, 7330	<i>Richard L. Crout</i>	4-8-2015
Division Head Ruth H. Preller, 7300	<i>Ruth H. Preller</i>	4/9/15
ADOR/Director NCST E. R. Franchi, 7000	<i>E. R. Franchi</i>	
Security, Code 1231	<i>Shannon Mensi</i>	4/20/15
Associate Counsel, Code 1008.3	<i>Shannon Mensi</i>	5-7-15
Public Affairs (Unclassified/Unlimited Only), Code 7030.4	<i>Shannon Mensi</i>	4-27-15
Division, Code		
Author, Code		
COMMENTS Need by 29 Apr 2015 This is a Final Security Review. Any changes made in the document, after approved by Code 1231, nullify the Security Review. 1. To the best knowledge of this Division, the subject matter of this publication (has <input type="checkbox"/>) (has never <input checked="" type="checkbox"/>) been classified. 2. This paper (does <input type="checkbox"/>) (does not <input checked="" type="checkbox"/>) contain any military critical technology. A copy of the paper, abstract or presentation is filed in this office.		

15 APR 15 10:27

Optical Turbulence in the Ocean (invited)

Weilin Hou

U.S. Naval Research Laboratory, Ocean Optics, Sensors and Systems, Stennis Space Center, MS 39529, USA

Abstract: The established view of diver visibility has been mainly focused on the effects of particles or turbidity of the water. The influence of optical turbulence due to variations of ocean temperature and salinity is shown to contribute to the degradation, through model and field validation. Lab setup of a simulated environment and future directions are also discussed.

OCIS codes: (010.7295) Visibility and imaging; (010.4450) Ocean optics; (010.7060) Turbulence

1. Introduction

Researchers of light transmission in the ocean have been long aware of the impact of optical turbulence on the signal transmission. While some might disagree with the term, as it is not the source of the turbulence, but rather the influences of temperature and/or salinity variations of the microstructures in the ocean, the effects have been observed and postulated to be mainly forward dominant. Classical works by several AGARD lecturers, such as Wells [1] discussed their impacts. Field demonstration showed that under extreme conditions, the degradation on image quality by optical turbulence can overtake that of turbidity [2]. Numerical simulations of small turbulence tank (30cm) also showed that the forward scattering can be orders of magnitude higher than the particle scattering, particularly in open oceans [3]. Efforts have been put in to quantify the turbulence process itself, by examining the scattering properties using existing sensor arrays such as wavefront sensor [3], although few quantitative results are available, to link the level of turbulence intensity to the optical signal transmission intensity. Directional change of polarization states have been examined in theory [4] and experiments [5], as a function of turbulence intensities, although concurrent measurements and model is still missing. Borrowing techniques from atmospheric turbulence research, we developed a theoretical model based on the modulation transfer function of the medium and turbulence, and subsequently validated by field efforts, which is discussed in Section 2. To better quantify this stochastic process, and develop means of mitigation, a controlled lab environment has been setup, to simulate various optical turbulence intensities by using a Rayleigh-Bénard convection tank. The tank is capable of generating and maintaining turbulence with Kolmogorov-type energy dissipation spectrum, as shown in Section 3. The tank setup has been guided by both numerical experiment using Large Eddy Simulation model, and measurements using acoustic Doppler velocimeter (ADV), and faster temperature probes. However, issues are abundant and require better lab measurements. A new type of sensor is under development and initial results are presented in Section 4.

2. SUIM and field validation

Little has been done in terms of quantifying the influence of underwater optical turbulence to signal transmission. A simple underwater imaging model (SUIM) was developed[6], based on similar approach from atmospheric optics, incorporating factors affecting the index of refraction (IOR) due to microstructure variations caused by temperature or/and salinity fluctuations in the ocean. Optical Transfer Functions (OTF), or Modulation Transfer Functions (MTF), are used when phase information is not a factor, to quantify the impacts from turbulence. Briefly, the combined effects from both turbidity and turbulence can be written as [6]

$$\begin{aligned}
 OTF(\psi, r)_{total} &= OTF(\psi, r)_{path} OTF(\psi, r)_{par} OTF(\psi, r)_{tur} \\
 &= \left(\frac{1}{1+D} \right) \exp \left[-cr + br \left(\frac{1 - e^{-2\pi\theta_0\psi}}{2\pi\theta_0\psi} \right) \right] \exp \left(-S_n \psi^{5/3} r \right) \\
 &= \left(\frac{1}{1+D} \right) \exp \left\{ - \left[c - b \left(\frac{1 - e^{-2\pi\theta_0\psi}}{2\pi\theta_0\psi} \right) + S_n \psi^{5/3} \right] r \right\}
 \end{aligned} \tag{1}$$

where $S_n = 1736 K_3 \lambda^{-1/3}$, and the $K_3 = B_1 \chi \epsilon^{-1/3}$. ψ is the angular spatial frequency Ψ and r is the transmission range. b , θ_0 and c are the scattering coefficient, mean scattering angle and beam attenuation coefficient, respectively. D is the normalized radiance, and the first term describes the effects of the path radiance. Utilizing Image Measurement

Assembly for Subsurface Turbulence (IMAST), we validated the above model during Skaneateles Optical Turbulence Experiment (SOTEX, [7]), and Bahamas Optical Turbulence Experiment (BOTEX, [7-9]).




Figure 1. Validation of SUIM. Left: field setup; Right: compared measurement to model results. Details see Hou et al, 2012.

3. Simulated Turbulence Environment

One of the main obstacles in studying turbulence is the stochastic nature of the process. In order to have a more controlled setting, we set up a simulated environment using a Rayleigh-Bénard (RB) convection tank (Fig.2). Heating and cooling are realized by two stainless steel plates with fluid flowing through at a preset temperature inside.




Figure 2. Rayleigh-Bénard convective tank setup (left) and numerical simulation results (right).

While the process itself can be seen actively generate turbulence, it is important to examine the energy dissipation scheme to ensure the setup follows naturally occurring mixing, such as the Kolmogorov type. Our analysis confirms such behavior, as shown in Fig. 3 ([10]).




Figure 3. Numerical model spectrum (left) and measurement results (right) confirm Kolmogorov spectrum slope of $-5/3$.

4. Better Sensing Capability

One of the issues quantifying the optical turbulence underwater is the difficulty obtaining high-speed, high-resolution data associated with the process. To overcome such challenge, we developed a novel temperature sensor, capable of 1kHz sampling with 1/1000 °C accuracy[11]. This is based on a fiber optics sensor head, using a silicon pillar attached to the end of the fiber. Figure 4 depicts the actual sensor and measurement from our RB tank.




Figure 4. A new novel fiber temperature sensor (left) and the measurement results from the RB tank, compared to two FP07s (marked "PMET"). Fiber sensors (ch1 -4) are placed within 5mm to nearby FP07.

5. Summary

We present a quick summary of optical turbulence research in the ocean, along with new modeling and measurement approach to mitigate the impacts on optical signal transmission. A quantified model can be used to estimate the optical turbulence vs turbidity on image degradation in the ocean. A simulated environment can be used to better examine the stochastic process, and means to mitigate such influence. Finally, a new thermometer is developed to better quantify the small scale fluctuations.

6. References

- [1] W. H. Wells, "Theory of small angle scattering," (NATO, 1973).
- [2] G. D. Gilbert and R. C. Honey, "Optical turbulence in the sea," in *Underwater photo-optical instrumentation applications*, (SPIE, 1972), 49-55.
- [3] D. J. Bogucki, J. A. Domaradzki, R. E. Ecke, and C. R. Truman, "Light scattering on oceanic turbulence," *Appl. Opt.* **43**, 5662-5668 (2004).
- [4] J. H. Churnside, "Polarization effects on oceanographic lidar," *Opt Express* **16**, 1196-1207 (2008).
- [5] S. Woods, J. Piskozub, W. Freda, M. Jonasz, and D. Bogucki, "Laboratory measurements of light beam depolarization on turbulent convective flow," *Applied Optics* **49**, 3545-3551 (2010).
- [6] W. Hou, "A simple underwater imaging model," *Opt. Lett.* **34**, 2688-2690 (2009).
- [7] W. Hou, S. Woods, E. Jarosz, W. Goode, and A. Weidemann, "Optical turbulence on underwater image degradation in natural environments," *Appl. Opt.* **51**, 2678-2686 (2012).
- [8] W. Hou, E. Jarosz, F. Dalgleish, G. Nootz, S. Woods, A. D. Weidemann, W. Goode, A. Vuorenkoski, B. Metzger, and B. Ramos, "Bahamas Optical Turbulence Exercise (BOTEX): preliminary results," in 2012), 837206-837206-837210.
- [9] S. Matt, W. Hou, S. Woods, E. Jarosz, W. Goode, and A. Weidemann, "Measurements of turbulent dissipation during the Bahamas Optical Turbulence Experiment," in 2013), 872405-872405-872410.
- [10] S. Matt, W. Hou, and W. Goode, "The impact of turbulent fluctuations on light propagation in a controlled environment," in 2014), 911113-911113-911111.
- [11] G. Liu, M. Han, and W. Hou, "High-resolution and fast-response fiber-optic temperature sensor using silicon Fabry-Pérot cavity," *Optics Express* **23**, 7237-7247 (2015).